

SQUAREDRAIN SHOWER INSTALLATION KIT WITH SHEET WATERPROOFING TECHNICAL SPECIFICATION

DESCRIPTION

The pre-sloped shower pan shall be a tileable shower receptor for point drains and made from extruded rigid PET (polyethylene terephthalate) plastic foam. It is strong, lightweight, non-reactive, chemically stable, UV resistant, and suitable for interior and exterior use. The pan can be used with both sheet membrane and liquid waterproofing and eliminates the need for traditional mud bed installations. The compressive strength shall be 145PSI and meet IAPMO PS-10 standards. It shall have the ability to be quickly modified to size on-site, is made from 100% post-consumer recycled plastic, and is fully recyclable.

APPLICATIONS/USES

- Industrial, commercial and residential showers
- Gang showers
- Pet Showers

SUITABLE SUBSTRATES (INTERIOR ONLY)

- Concrete
- Exterior glue plywood
- Cement backer board**
- OSB or Avantech

**Consult cement backer board manufacturer for specific installation recommendations

APPROVALS AND LISTINGS

Before installing the QuickDrain system, check with your local building department/plumbing inspector to ensure compliance with the local building codes. QuickDrain is not responsible for any conflicts with local building codes or improper installation of any part of the assembly or the waterproofing membrane. Dimensions are subject to manufacturer's tolerance and can change without notice.

Job Name Location	Item #
Engineer	_ Contractor
P0 #	Tag
Representative	



INSTALLATION KIT INCLUDES

- Pre-sloped shower pan
- Pre-formed PET curb & lag screws
- Sheet waterproofing & accessories
- Small or large universal flange adaptor
- Weep guard
 - Drain base sold separately

PRODUCT SELECTOR

EXAMPLE: SDPAN-SWP38X60-SFOFF SQUAREDRAIN SHOWER INSTALLATION KIT INCLUDING SHEET WATERPROOFING MEMBRANE, 38"X60" PRE-SLOPED SHOWER PAN, AND SMALL UNIVERSAL FLANGE ADAPTOR FOR 4" DRAINS IN AN OFFSET DRAIN LOCATION

J	DPAN	- 5	5W	Ρ	-			
Р	SquareDrain Pre-sloped Pan Kit		eet Membra Vaterproofin	Don Sizo	-	Jniversal 1ge Adaptor	Drain Location	
\checkmark	PAN SIZE	\checkmark	UNIVERSAL FLANGE ADAPTOR		\checkmark	DR	DRAIN LOCATION	
	48"x48"		SF =	Small for 4" SquareDrain			Centered	
	38"x60"		LF =	Large for 5" and 6" SquareDrain			Offset	

Access BIM/Revit content through www.oatey.com

Oatey Co. | 20600 Emerald Parkway, Cleveland, OH 44135 | P: 1.800.321.9532 | oatey.com

Data is subject to manufacturing tolerances.