



# QUICKDRAIN SHEET MEMBRANE WATERPROOFING KITS TECHNICAL SPECIFICATION

Job Name _____	Item # _____
Location _____	
Engineer _____	Contractor _____
PO # _____	Tag _____
Representative _____	

## DESCRIPTION

Topical sheet membrane waterproofing and accessories shall be used in residential and commercial applications when creating a watertight shower pan or shower system. Sheet waterproofing must be installed a minimum of 4" above flood rim in a shower pan and can be used to waterproof walls within shower footprint or other surfaces with tile/stone application. Meets ANSI A118.10 and holds IAPMO Listing #8483.

## WATERPROOFING KIT INCLUDES

- QTS Sheet Membrane
- Curb Covers (for curbed shower pans)
- Outside Corners (for ADA, curbless shower pans)
- Inside Corners
- QDMUS (sealant)

## APPLICATIONS/USES

- Industrial, commercial and residential showers
- Gang showers
- Pet Showers

## APPROVALS AND LISTINGS

Before installing QuickDrain USA system, check with your local building department/plumbing inspector to ensure compliance with the local building codes. QuickDrain USA LLC is not responsible for any conflicts with local building codes. QuickDrain USA LLC is not responsible for improper installation of any part of the assembly or the waterproofing membrane. Dimensions are subject to manufacturer's tolerance and can change without notice.



## PRODUCT SELECTOR

SHEET MEMBRANE WATERPROOFING KITS						
✓	Size	Item Code	Kit Components			
			Curb Covers	Outside Corners	Inside Corners	QDMUS Sealant
	52" x 78"	SDSWP36	2	-	4	1
	64" x 78"	SDSWP48	2	-	4	1
	60" x 78"	SLSWP-ADA	2	2	-	1

Access BIM/Revit content through [www.quickdrainusa.com](http://www.quickdrainusa.com)